

eS1x2TBOD60

E-scooter rack 2 spaces double-sided, T floor stand 60

VIEW



SIDE VIEW



TECHNICAL DATA

Item	**eS1x2TBOD60**
GTIN	9120120491029
Users	E-scooters and kick scooters
Parking spaces	2 (double-sided)
Length	120 mm

Mounting height	approx. 60 cm (recommended for e-scooters)
Space opening	approx. 80 × 70 mm
Fixing	1 × T floor stand 60
Material	Steel, hot-dip galvanised to DIN EN ISO 1461
Weight	6 kg

SHORT TEXT

E-scooter rack 2 spaces double-sided, T floor stand 60

LONG TEXT · UNIT PCS

E-scooter rack for the orderly, lockable parking of e-scooters and kick scooters. 2 parking spaces: two single holders arranged double-sided (facing each other), parking position secured via the steering column. Each space with a pivoting locking bar, lockable with a standard commercial padlock (shackle Ø up to 6 mm) or the user's bicycle lock; space opening approx. 80 × 70 mm.

Steel construction, hot-dip galvanised to DIN EN ISO 1461, silver-grey finish.

Holder length 120 mm, mounting height approx. 60 cm (recommended for e-scooters) above finished floor level.

Fixing with 1 × T floor stand 60 for anchor fixing (base plate 140 × 50 mm, 2 holes Ø 11 mm per plate, hole spacing 90 mm) to a load-bearing substrate, including fixings.

Supply as a complete kit including connecting bolts and installation instructions, and install in accordance with the manufacturer's instructions.

Reference product: Rollerstop GmbH, Himmelpfortgasse 13/6, 1010 Wien, www.rollerstop.com, type eS1x2TBOD60 or equivalent.

Criteria of equivalence: number and arrangement of parking spaces, individual pivoting locking bar per space, rail length, mounting height, hot-dip galvanised finish, fixing method.

Product offered: '.....'